The Largest Manufacturer of U

The Largest Manufacturer of Worm-drive Hose Clamps in Southern Africa.

5



The re-usable FlipTop worm-drive hose clamp is suitable for all plastic and rubber hoses.

The Flip-Top design with flexible band facilitates a "Quick'n Easy" fitting of the clamp in restricted or difficult applications, especially where the clamp has to be opened for installation.

It also has no spot welding and is designed to exert increasing closing pressure as more torque is applied to the screw.

The screw thread fully penetrates the perforated band, increasing the clamp's strength and reducing the chance of it working lose.

"GSS" SERIES STAINLESS STEEL CLAMP

The fully stainless steel "GSS" series FlipTop clamp comprises of a 300 series stainless steel housing, band and slotted 8mm hex-head screw. It is ideally suited to mining, marine, swimming pool, agricultural and chemical applications where corrosion resistance and durability are critical.

It is also used in the electrical and telecommunications industry on cable applications.

"GS" SERIES COMPOSITE CLAMP

The "GS" Series Composite FlipTop clamp consists of a 400 series stainless steel band, with zinc electroplated mild steel housing and slotted 8mm hex-head case-hardened screw.

It is ideally suited for Automotive applications and general environments.

Our company's policy is one of continuous product innovation, and we reserve the right to change specifications without notice. Any such changes would benefit customers and be driven

by our response to market requirements and changing specifications





Clamps that Torque-up & Grip-Tight. Hoses know! University and the Grip Reg No 2006/107878/23

* LARGER SIZES AVAILABLE ON REQUEST ** MAXIMUM RECOMMENDED TORQUE

MANUFACTURED IN SOUTH AFRI	
rip-Tight. Hoses know!	Stant Managana
Reg No 2006/107878/23	
s@uniclips.co.za	Certified by DQS ISO/TS16949 ISO 9001 Ber No. 327896

Fa	Factory Street, Industria North, Johannesburg							
0	Box	58124,	, Newvil	le, 2114	•	E-mail:unicl	ips@uniclips	.co.za
el:	+27	11 47	7-1310	Telefax:	+27	11 477-764	42 / 7476	

A C B D	Dimensions mm inches					
	Α	31.3	1.1/4			
F	В	9.5	3/8			
	С	17.3	11/16			
G	D	8.0	5/16			
	Е	12.0	15/32			
	F	12.0	15/32			
F	G	#see	below			

DIAMETER RANGE - G*				
CODE		mm		Torque**Nm
HSGSS 8	HSGS 8	14-27	%6 - 1 1/16	5.0
HSGSS12	HSGS12	14-32	‱ - 1 ¼	5.0
HSGSS16	HSGS16	17-38	¹ / ₁₆ - 1½	5.0
HSGSS 20	HSGS 20	19-44	<u>34</u> - 134	5.0
HSGSS 24	HSGS 24	25-51	1 - 2	6.0
HSGSS 28	HSGS 28	32-57	1¼ - 2¼	6.0
HSGSS 32	HSGS 32	38-63	1½ - 2½	6.0
HSGSS 36	HSGS 36	44-70	1¾ - 2¾	6.0
HSGSS 40	HSGS 40	51-76	2 - 3	7.0
HSGSS 44	HSGS 44	57-82	2 ¼ - 3¼	7.0
HSGSS 48	HSGS 48	63-89	2½ - 3½	7.0
HSGSS 52	HSGS 52	70-95	2 ¾ - 3¾	7.0
HSGSS 54	HSGS 54	72-98	2 ¹³ /16 - 3 ¹³ /16	7.0
HSGSS 56	HSGS 56	76-102	3 - 4	7.0